



# ENEOS Premium Ultra 0W20

## Fully Synthetic Ultimate Performance Gasoline Motor Oil

The ultra-advanced, low viscosity engine oil which has been engineered in response to the Japan's Ministry of Land, Infrastructure and Transport low-emissions certification system introduced in order to protect natural environment by promoting the use of automobiles with reduced emissions. Under this system in Japan, low-viscosity Motor Oils are recommended for use to support low-emission in vehicles, through best fuel economy & environmental performance. Since the system's adoption, automobile makers have been progressing in designing of low-emission engines in vehicles. ENEOS Premium Ultra 0W20 is the next generation of ENEOS's flagship product with upgraded API SN specification and it is environmentally friendly Gasoline Motor Oil that provides extremely good fuel economy. Blended with extra exceptional performance organic molybdenum friction-reducing additives, this oil minimizes engine friction at cold temperatures, has got extreme hot temperature stability, less volatility and low viscosity of 0W-20.

### FEATURES & BENEFITS

#### 1. Low Viscosity (0W-20)

This Oil is blended from high-performance synthetic base oils and optimized additive blend including molybdenum, so it provides much better thermal & oxidation stability, but also improved friction reduction characteristics than regular Motor Oils. Thanks to its innovative formulation, this Oil achieves a low viscosity of 0W-20, so it enables excellent fuel economy and environmental protection.

#### 2. Ultra low Fuel Economy

Specially formulated additives reacts with metal surfaces and form lubricated film even under boundary lubrication conditions, protecting your engine against wear & tear. As a result, this oil minimizes friction and enables superb fuel economy.

#### 3. Overall Engine Protection

Active Cleaning agents (Metal Detergents and Ash-less Dispersants) prevent sludge & deposits build-up for a longer and cleaner engine life

### PERFORMANCE LEVELS

- API SN
- ILSAC GF-5

### APPLICABLE VEHICLES

- All Japanese cars with Gasoline Engines filled with SAE 0W-20 oil or lower as the Factory fill and engines for which .SAE 0W-20 viscosity grade is recommended.

*Caution:* The use of this oil in automobiles designed for high-viscosity oils can result in inadequate oil circulation, oil leaks, and other problems.

### PACK SIZES

1L, 4L, 60L, 208L

### TYPICAL PROPERTIES

SAE viscosity grade	0W-20
Density (20°C), g/cm <sup>3</sup>	0.850
Flash point (COC), °C	224
Kinematic viscosity (40°C), mm <sup>2</sup> /s	47.22
(100°C), mm <sup>2</sup> /s	8.76
Viscosity index	167
Pour point, °C	-45

Note: The typical properties may be changed without notice. (September 2014)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.